



Powerful, feature rich & simple thin client desktop

Supporting Microsoft Terminal Services & Citrix MetaFrame with the lowest cost of ownership.

* Monitor not included

Key Business Benefits

- + Annual cost saving across the business
- + Reduce total cost of ownership (TCO)
- + Increase return on investment (RoI)
- + Reduce support costs
- + Reduce desktop maintenance costs
- + Virtually eliminate desktop upgrades
- + Standardisation of the desktop
- + Easy hot-desking and roaming profiles
- + Centralised management and control
- + Remove viruses from the desktop
- + Reduce training costs
- + Easy deployment for remote offices
- + Application delivery on-demand
- + Aligns with corporate IT strategy
- + Reduces risk of data loss or theft
- + Cost effective alternative to PCs

Infrastructure Features

- + Supports Windows 200x servers
- + Citrix MetaFrame
- + Multi-session support

Technical Features

- + 300Mhz PI class processor
- + Microsoft Windows CE.NET operating system
- + 10/100mps network port
- + Highly expandable device
- + Many USB options
- + Wireless support
- + Slim line design
- + Very low energy consumption

The Netvoyager Neterm thin client desktops are the ideal method to deliver applications on-demand using server-based computing.

The Neterm CE1010 is a simple, feature rich and plug-n-play thin client desktop packing 300Mhz of processing power, all in a device significantly smaller than a traditional PC.

The Neterm CE1010 includes remote session support for Microsoft and Citrix, wireless support, security and manageability all powered by the latest Microsoft Windows CE.NET operating system.

The Neterm CE1010 offers expansion using two USB ports and legacy port support. The Neterm, like all other Netvoyager thin client desktops are remotely managed using the Netvoyager InFocus enterprise management tool.

A perfect desktop solution for those requiring a complete centralised system. Netvoyager thin clients are a more efficient way to deliver Windows® applications, specifically to function oriented and general office users were lower cost of ownership, simplicity, manageability and security are paramount.

Netvoyager thin clients are ideal for healthcare, call centre, manufacturing, and education environments.

Whether its for a remote site or local use, the Netvoyager Neterm CE1010 plugs straight into your network and to your server-based computing infrastructure without any requirement for significant configuration.

A complete industry standard plug-n-play desktop solution which is user-friendly, requires no application installations and is virus protected.



Server-based Computing Protocols

- + Microsoft RDP
- + Citrix ICA
- + ThinPrint®

Platform Specifications

- + 300Mhz
- + 32MB RAM
- + 8MB Flash
- + Windows CE.NET 5 operating system

Video Platform

- + VESA monitor support
- + Resolution upto 1280 x 1024
- + Referesh rate upto 85hz
- + Colour depth upto 16-bits

Audio

- + Full 16-bit audio with stereo audio out ports

Network Features

- + 10/100Mbps Fast Ethernet
- + TCP/IP, DNS & DHCP support
- + Multiple master ICA browser support
- + Citrix ICA load balancing support
- + Point-to-Point Protocol (PPP)
- + VPN Support
- + SNMP support for remote management

Connectivity Ports

- + RJ-45 ethernet port
- + 15-pin D-plug VGA port
- + Composite & S-video output
- + 15-pin D-plug parallel port
- + 9-pin D-plug serial ports
- + PS/2 keyboard & mouse ports
- + 2 x USB 1.1 ports
- + Stereo audio output ports

External Indicators

- + Power indicator
- + LAN activity indicator
- + Flash activity indicator

Accessories

- + External USB floppy drive
- + External USB flash drives
- + External USB WiFi 802.11b NIC

Server OS Compatibility and Support

- + Microsoft .Net Server ready
- + Microsoft Windows 2000
- + Microsoft Windows NT4 Server Terminal Server
- + Citrix Winframe, Metaframe and XP
- + Multi-language keyboard support

Configuration and Management

- + Remote device shadowing
- + Kiosk mode
- + Remote management w/Netvoyager InFocus

Electrical Features

- + Internal universal power supply
- + 110-240V AC supported
- + 40W power consumption

Physical Features

- + Weight: 2.10kg
- + Height: 55mm
- + Width: 315mm
- + Depth: 245mm

Warranty Support

- + 3 years return to base
- + Applicable only with online registration within 60 days of purchase
- + Premium support contracts available

Environmental Specifications

- + Temperature Range: 0°C to 40°
- + Humidity Range: 20% to 80% non-condensing

Compliance

- + FCC, CE, TUV, UL