

#### Monitor not included

# The powerful and feature rich slim line thin client desktop

One solution supporting Microsoft Windows and Unix/Linux application servers and with the lowest cost of ownership.

**Key Business Benefits** 

- + Annual cost saving across the business
- + Reduce total cost of ownership (TCO)
- + Increase return on investment (RoI)
- + Reduce support & maintenance costs
- + Supports Windows & Unix application servers
- + Virtually eliminate desktop upgrades
- + Standardisation of the desktop
- Easy hot-desking and roaming profiles
- + Centralised management and control
- + Remove viruses from the desktop
- Reduce training costs
- + Easy deployment for remote offices
- Application delivery on-demand
- + Aligns with corporate IT strategy
- + Reduces risk of data loss or theft
- + Cost effective alternative to PCs

# **Infrastructure Features**

- + Supports Windows 200x servers
- + Citrix MetaFrame, WinFrame, Presentation Server
- + Tarantella Enterprise
- + Native X Windows (X11)
- + VNC, ShellScript, SSH, Telnet and Terminal emulation
- + Multi-session, multi-window support

## **Technical Features**

- + 800Mhz Intel processor
- + 256MB RAM & 128MB Flash
- + Powerful graphics engine
- + Netvoyager Lithium<sup>™</sup> embedded Linux-based OS
- + 10/100Mbps network port
- + Many USB options
- + Silent and slim line design
- + Very low energy consumption
- + 2 year RTB warranty

The Netvoyager Neterm thin client desktops are the ideal method to deliver applications on-demand using server-based computing.

Designed with simplicity in mind, suitable for delivering office and administrative applications seamlessly.

The Neterm LX1010 is a powerful thin client desktop solution that is suitable for environments that require a wide variety of application server support and emulation connectivity. The LX1010 provides all this in a small desktop device which is remotely manageable.

As standard the Neterm LX1010 includes remote session support for Microsoft, Citrix, Tarantella and X11 servers, SSH and terminal emulation, wireless support, security and manageability in a very small desktop footprint.

The Neterm LX1010 offers unparalleled expansion using USB ports and legacy port support. The Neterm, like all other Netvoyager thin client desktops are remotely managed using the Netvoyager InFocus enterprise management tool as well as direct connection from a remote browser.

The Netvoyager Neterm LX1010 is the perfect single desktop strategy to access homogenous networks with multiple systems such as Windows and Unix systems. With powerful graphics and stereo sound, there is no compromise in productivity features.

Whether its for a remote site or local use, the Netvoyager Neterm LX1010 plugs straight into your network and to your server-based computing infrastructure without any requirement for significant configuration.

A complete industry standard plug-n-play desktop solution which is user-friendly, requires no application installations and is virus protected.

A desktop solution with a very low total cost of ownership (TCO) and a high return on investment (RoI) ratio.







© 1999 - 2005, Netvoyager plc. All rights reserved. Netvoyager®, NVTV® are registered trademarks of Netvoyager plc. Citrix®, MetaFrame®, MetaFrame XP™ and Citrix Solutions Network™ are registered trademarks or trademarks of Citrix Systems, Inc. Microsoft®, Windows® and Windows NT® are registered trademarks of Microsoft Corporation. UNIX® is a registered trademark of The Open Group. All other trademarks and registered trademarks are property of their respective owners.



# Server-based Computing Protocols & Applications

- + Microsoft RDP, Citrix ICA, Tarantella AIP, VNC
- Integrated Mozilla Firefox Browser with Java VM Citrix Web Services, Adobe Flash and PDF support
- + X-Windows (X11), Terminal Emulation
- + ThinPrint<sup>®,</sup> NFS/Samba support
- + Telnet, SSH, Local ShellScript support

# **Platform Specifications**

- + 800Mhz Via Eden CPU w/MMX & 3DNow
- + 256MB RAM
- + 128MB Flash
- + Netvoyager Lithium<sup>™</sup> Operating System

# **Video Platform**

- + AGPx4 2D/3D graphics processor with MPEG2 accelerator
- Resolutions supported: 640x480, 720x480, 720x576, 800x600, 848x480, 1024x512, 1024x768, 1152x864,1152x900, 1280x720, 1280x768, 1280x1024, 1368x768, 1440x1050, 1600x1200
- + Refresh rate up to 85hz
- + Colour depth up to 24-bits

# Audio

- + Full 16-bit audio
- + Microphone and stereo out ports

# **Network Features**

- + Auto-sensing 10/100Mbps Fast Ethernet
- + TCP/IP, DNS & DHCP support
- + Multiple master ICA browser support
- Citrix ICA load balancing support
- + Point-to-Point Protocol (PPP)
- + PPTP VPN Support
- + SNMP support for remote management

# **Connectivity Ports**

- + RJ-45 ethernet port
- + PS/2 keyboard & mouse ports
- + 2 x USB 2.0 ports
- + Mic line-in and stereo-out jacks

# **External Indicators**

- + Power indicator
- ROM activity indicator
- + LAN activity indicator

## **Optional Accessories**

- + External USB floppy drive
- + External USB flash drives
- + External USB WiFi 802.11b NIC
- + External USB/Serial PSTN modem
- + USB based touch screen

## Server OS Compatibility and Support

- + Microsoft .Net Server ready
- + Microsoft Windows 2000, 2003 and 2008
- + Microsoft Windows NT4 Server Terminal Server
- + Citrix Winframe, Metaframe, XP and Presentation Server
- + Tarantella Enterprise 3 Server
- + Unix Variants (Linux, Solaris)

# **Configuration and Management**

- + Remote device shadowing
- + Kiosk or desktop mode
- + Remote management w/Netvoyager InFocus
- + Multi-language keyboard support
- + Configurable session auto-login
- + Multi-session, Multi-protocol, Multi-window support

### **Electrical Features**

- + External universal power supply
- + 110-240V AC supported
- + 18W power consumption

## **Physical Features**

- + Weight: 0.78kg
- + Dimensions: H 170mm x W 124mm x D 38mm

# Warranty Support

- + 2 years return to base
- Applicable only with online registration within 60 days of purchase
- + Premium support contracts available

# **Environmental Specifications**

- + Temperature Range: -20°C to 60°
- + Humidity : 0% to 85% relative humidity, non-condensing

# Compliance

+ FCC, CE, VCCI

\* Specifications are subject to change, at any time, without notice.



NETVOYAGER PLC Telephone: +44(0)845 108 3030 Sales: sales@netvoyager.co.uk